


Device Modeling Report

COMPONENTS:MOSFET: OPERATIONAL AMPLIFIER
PART NUMBER:NJM2140
MANUFACTURER: NEW JAPAN RADIO CO.,LTD



Bee Technologies Inc.

Spice Model




```

*$
* PART NUMBER:NJM2140
* MANUFACTURER: NEW JAPAN RADIO
* All Rights Reserved Copyright (c) Bee Technologies Inc. 2005
.Subckt NJM2140 OUT1 -IN1 +IN1 V- +IN2 -IN2 OUT2 V+
X_U1  +IN1 -IN1 V+ V- OUT1 NJM2140_ME
X_U2  +IN2 -IN2 V+ V- OUT2 NJM2140_ME
.ends  NJM2140
*$
.subckt NJM2140_ME 1 2 3 4 5
c1  11 12 1.0000E-12
c2  6 7 27.500E-12
dc  5 53 dy
de  54 5 dy
dlp 90 91 dx
dln 92 90 dx
dp  4 3 dx
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
fb  7 99 poly(5) vb vc ve vlp vln 0 173.94E3 -1E3 1E3 170E3 -170E3
ga  6 0 11 12 2.2996E-3
gcm 0 6 10 99 458.84E-9
iee 3 10 dc 120.20E-6
hlim 90 0 vlim 1K
q1  11 2 13 qx1
q2  12 1 14 qx2
r2  6 9 100.00E3
rc1 4 11 434.85
rc2 4 12 434.85
re1 13 10 3.7735
re2 14 10 3.7735
ree 10 99 1.6639E6
ro1 8 5 50
ro2 7 99 25
rp  3 4 78.272
vb  9 0 dc 0
vc  3 53 dc 1.0979
ve  54 4 dc 1.0979
vlim 7 8 dc 0
vlp 91 0 dc 20
vln 0 92 dc 20
.model dx D(Is=800.00E-18)
.model dy D(Is=800.00E-18 Rs=1m Cjo=10p)
.model qx1 PNP(Is=800.00E-18 Bf=546.95)
.model qx2 PNP(Is=828.3277E-18 Bf=650.05)
.ends
*$


```

Output Voltage Swing, +Vout and -Vout

Simulation result




Evaluation circuit




Output Voltage Swing	Data sheet	Simulation	%Error
+Vout(V)	2.200	2.200	0.000
-Vout(V)	-2.200	2.200	0.000

Input Offset Voltage

Simulation result




Evaluation circuit




Vos	Measurement		Simulation		Error	
	1	mV	1.029	mV	2.900	%

Slew Rate, +SR, -SR

Simulation result




Evaluation circuit




Slew Rate(v/us)	Data sheet	Simulation	%Error
	4V/us	4.070V/us	1.750

Input current Ib, Ibos

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
Ib(nA)	100.000	100.349	0.349
Ibos(nA)	10.000	9.902	-0.980

Open Loop Voltage Gain vs. Frequency , Av-dc, f-0dB

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
f-0dB(MHz)	12	11.533	-3.892
Av-dc(dB)	80	79.973	-0.034

Common-Mode Rejection Voltage gain

Simulation result



Evaluation circuit



Common Mode Reject Ratio= $9927.73/2.001=4961.384$

CMRR	Data sheet	Simulation	%Error
	74.000	73.912	-0.119