


Device Modeling Report

COMPONENTS: OPERATIONAL AMPLIFIER
PART NUMBER: NJM2721
MANUFACTURER: NEW JAPAN RADIO CO., LTD



Bee Technologies Inc.

Spice Model




```

*$
* PART NUMBER:NJM2721
* MANUFACTURER: NEW JAPAN RADIO
* All Rights Reserved Copyright (c) Bee Technologies Inc. 2006
.Subckt NJM2721 OUT IN- IN+ V+ V-
X_U1  IN+ IN- V+ V- OUT NJM2721_ME
.ends NJM2721
.subckt NJM2721_ME 1 2 3 4 5
c1  11 12 10.6603E-12
c2  6 7 30.000E-15
dc  5 53 dy
de  54 5 dy
dlp 90 91 dx
dln 92 90 dx
dp  4 3 dx
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
fb  7 99 poly(5) vb vc ve vlp vln 0 1.7684E3 -1E3 1E3 1E3 -1E3
ga  6 0 11 12 22.619E-3
gcm 0 6 10 99 2.2619E-6
iee 3 10 dc 15.030E-3
hlim 90 0 vlim 1K
q1  11 2 13 qx1
q2  12 1 14 qx2
r2  6 9 100.00E3
rc1 4 11 44.210
rc2 4 12 44.210
re1 13 10 40.680
re2 14 10 40.680
ree 10 99 13.307E3
ro1 8 5 50
ro2 7 99 25
rp  3 4 38.172
vb  9 0 dc 0
vc  3 53 dc 1.9479
ve  54 4 dc 1.9479
vlim 7 8 dc 0
vlp 91 0 dc 20
vln 0 92 dc 20
.model dx D(Is=800.00E-18)
.model dy D(Is=800.00E-18 Rs=1m Cjo=10p)
.model qx1 PNP(Is=800.00E-18 Bf=497.59)
.model qx2 PNP(Is=894.9214E-18 Bf=502.43)
.ends
*$


```

Output Voltage Swing

Simulation result




Evaluation circuit




Output Voltage Swing	Data sheet	Simulation	%Error
+Vout(V)	1.350	1.336	-1.037
-Vout(V)	-1.350	-1.336	-1.037

Input Offset Voltage

Simulation result




Evaluation circuit




Vos	Measurement		Simulation		Error	
	3.000	mV	3.020	mV	0.667	%

Slew Rate

Simulation result




Evaluation circuit




Slew Rate(v/us)	Data sheet	Simulation	%Error
	500.000	512.000	2.400

Input current

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
Ib(uA)	15.000	14.919	-0.540
Ibos(uA)	0.150	0.149	-0.667

Open Loop Voltage Gain vs. Frequency

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
f-0dB(MHz)	120.000	124.524	3.770
Av-dc	60.000	59.362	-1.063

Common-Mode Rejection Voltage gain

Simulation result



Evaluation circuit



Common Mode Reject Ratio= $929.180/0.099=9385.659$

CMRR	Data sheet	Simulation	%Error
	80.000	79.449	-0.689